

SA-AD1
SA-AD2

SA-AD1 or AD2 Individual Temperature Alarm with Communications For your Laboratory Requirements

SA-AD1 & SA-AD2 ► STAND ALONE ALARM & COMMUNICATIONS

- ◆ Compact size. 250H x 160W x 40D (mm)
- ◆ Simple to use.
- ◆ Inputs available : Temperature
- ◆ Temperature range -200°C to $+100^{\circ}\text{C}$.
- ◆ Temperature Alarm resolution 0.1°C .
- ◆ Temperature Alarm accuracy better than 0.1°C across the full range, plus probe accuracy.
- ◆ Front panel selectable display of temperature, time delay, unit number ID and alarm parameters.
- ◆ Temperature high alarm.
- ◆ Temperature low alarm.
- ◆ Audible and visual indication of an alarm.
- ◆ Adjustable time delay for temperature alarm. (0 to 90 minutes)
- ◆ Mains power failure alarm.
- ◆ Status and alarm indication on transmitter.
- ◆ Volt free contact output available.
- ◆ Rechargeable battery backup.
- ◆ SD1 + Auto-dialler with up to 4 telephone numbers dialed.

The SA-AD2 has all the features of the SA-AD1 with the added facility to phone 10 numbers.

